



12-ft Weighted Wattle
50 pounds



3-ft Gutter Wattle
30 pounds



8-ft Drain Wattle
50 Pounds



**33-in Curb Cutout
Protector 1Pound**

FOR USE ON ASPHALT & CONCRETE

- SURVIVE TIRES AND TRACKS
- TRIPLE WRAPPED SAND IN MONOFILAMENT GEOTEXTILE
- NO ADHESIVES OR FASTENERS NEEDED
- NO ROCKS FROM BROKEN ROCK BAGS
- EASY TO MOVE, CLEAN AND REPLACE
- REUSABLE ON SEVERAL PROJECTS

Weighted Wattles are designed for direct placement on hard surfaces such as parking lots and roadways during construction to contain runoff, allowing the cleaner water to pass while holding back sediment. Connect end-to-end for continuous protection.

Weighted Gutter Wattles are placed diagonally across the gutter upstream from storm drains to form a small settling pond, allowing the cleaner water to pass and sediment and trash to drop out.

Weighted Drain Wattles are designed for direct placement on asphalt and concrete around or across storm drains. The 2-foot weighted ends placed perpendicular to the curb cause water to pond in the gutter allowing sediment, trash and leaves to settle out for easy cleanup. The lightweight rigid foam filled 4-foot center portion allows cleaner water to pass underneath into the storm drain, while holding back trash. Use alternate install configurations to fit your needs.

Curb Cutout Protectors are placed across curb cutouts to allow major stormwater to pass through the geotextile into the storm drain overflow while preventing construction site trash from entering the drain overflow. Install the apron under the storm drain grate to hold it firmly against the curb. Shaped Foam inside woven monofilament geotextile allows maximum flow.

NOT ON YOUR PLANS – Write in Gator Guard products on your SWPPP as an equal or better BMP, sign and date. (if in-doubt, check with your engineer, contract administrator and/or agency official first)

Street & Drain Sediment Control Installation & Maintenance

Weighted Wattle

1. Take to desired location, remove the bands and unfold. **DO NOT DRAG.**
2. Push the weighted inserts fully into the outer sock.
3. Soft Geotextile should be centered on the bottom – reposition inserts to get weighted side down if necessary.
4. Connect by pushing the closed end of one Wattle fully into the open end of the next. Handling straps may be tied together for a more secure connection.

Weighted Gutter Wattle

1. Place Gutter Wattle Diagonally across gutter and press into place with your feet.

Weighted Drain Wattle

1. Install per photos **below**. Press sandbags with feet – tight to curb. **DO NOT DRAG**
2. Inspect weekly for correct placement
3. REUSE or dispose of wattle properly if damaged, deteriorated or no longer needed.



Most Effective Install



Stops Dirt & Covers Curb Cutout



Covers Curb Cutout

Curb Cutout Protector

1. Remove storm drain grate and place it on the sidewalk. Clean the framework.
2. Place Drain Inlet Bag in the opening and hold with your feet
3. Center the Curb Cutout Protector against the curb with apron either under or over the DI Bag and hold the ends with your feet too.
4. Install the grate on top of the DI bag and curb cutout protector apron. Pull the apron ends tight while holding up the back of the grate, then push down on the grate until flush.

MAINTENANCE

1. Inspect, clean out deposited sediment after each storm event (best to sweep when dry).
2. REUSE or dispose of properly if damaged, deteriorated or no longer needed.

Street & Drain Sediment Control SPECIFICATIONS



12-ft Weighted Wattle



3-ft Gutter Wattle



8-ft Drain Wattle



33-in Curb Cutout

	WEIGHTED WATTLE	GUTTER WATTLE	DRAIN WATTLE	CURB CUTOUT PROTECTOR
Part No.	EWW612	WGW436	WDW608	CCP433
Height	6-inch	4-inch	6-inch	4-inch
Length	12-ft (+ sleeve)	36-inch	8-feet	33-inch effective
Connection Sleeve	20-inch	none	none	none
Weight	50-pounds	30-pounds	50-pounds	0.75-pounds
Pallet Weight	740-lb (14 ea.)	1240-lb (40 ea.)	1290-lb (25 ea.)	120-lb (108 ea.)
Full Pallet - Inches	48x42x38	42x42x34	48x48x38	48x48x65 (108ea)
Single Bundle In.	48x18x6	37x10x4	48x12x6	45x15x15 (9 ea)
Outer Construction				
- Main Fabric	6-oz Woven Monofilament Polypropylene			
- Bottom-nonwoven	Polypropylene	none	Polypropylene	none
- Straps	1-inch 900-lb UV Polypropylene Webbing			none
- Poly Strapping	none	none	Polypropylene	none
Inner Construction				
- Weight Material	Clean Coarse Sand			none
- Inner Sand Bag	6-mil Polyethylene			none
- Sand Bag Cover	6-oz Woven Monofilament Polypropylene			none
- Foam for Height	2"x4"x45"	none	6" x 45" roll	33"x4"x4" shaped
Woven Fabric				
- Type	High Quality Woven Monofilament Silt Fence			
- Weight	6 oz./sq. yd.			
- Tensile Strength	375 x 250 lbs.			
- Puncture	120 lbs.			
- Water Flow	100-gpm/sf clean water, <10-gpm/sf dirty water			
- UV % Strength	90% after 500 hrs.			
Thread				
	UV Resistant Polyester			
Functional Life				
	5 years expected (excludes major damage)			

Date: April 2020 – The above properties are typical averages. All test methods are ASTM or Industry Standards.